



Myoelectric Hands Myo Select

Products Characteristics/产品特性

- Controlled with myoelectrodes or switch inputs
- Electronics equipped with patented Powerforce™ technology
- Supercapacitor technology (sizes 7¼ - 8 ¼) provides efficient control and power conservation
- Nine control modules
- Electronic 'gear change'
- 2 wrist options available; Quick Disconnect Wrist and Friction Wrist
- 2 thread options available; North American Thread (1/2 x 20 TPI) and European Thread (M12 x 1.5mm)
- 通过电极或开关控制
- 配备Powerforce™专利技术的电子设备
- 超级电容器技术（尺寸为7¼-8¼）控制力强而且节能
- 九种控制模式
- 电子切换不同模式
- 两种腕关节可选：EQD（快速拆卸腕关节）和摩擦腕关节
- 两种螺纹可选：北美螺纹(1/2 x 20 TPI) 和欧洲螺纹(M12 x 1.5mm)

Technical parameters/技术参数

尺寸 size	速度 (秒) Speed	握力 (磅力) Grip Strength	最大开合度 (毫米) Max Opening	重量 (含内置手套) Weight with inner glove	长度 (从手壳下端到拇指尖) Length (Base Hand Shell to Thumb Tip)	运行电压 (伏) Operating Voltage
6 ¼	1.5 seconds	40N (9.5lbf)	65mm (2 5/8")	320g (11oz)	116mm (4 1/2")	7.2V DC
7 ¼	0.8 seconds	80N (19lbf)	100mm (4")	470g (1lb)	140mm (5 1/2")	7.2V DC
7 ¾	0.8 seconds	80N (19lbf)	100mm (4")	510g (1lb 2oz)	143mm (5 5/8")	7.2V DC
8 ¼	0.8 seconds	80N (19 lbf)	100mm (4")	520g (1lb 2oz)	147mm (5 3/4")	7.2V DC

Exclusive Agent of China
中国独家总代理

上海迪萨假肢矫形器有限公司

SHANGHAI DISAN PROSTHETIC & ORTHOPAEDIC CO., LTD

地址 (Add): 上海市杨浦区安波路533弄
免费客服热线(Hot Freeline): 400-920-6789
E-mail: de-disan@de-disan.com

电话 (Tel): 021-55218636
传真 (Fax): 021-55123213
http://www.de-disan.com